



#### NOTES, UNLESS OTHERWISE SPECIFIED

1. REMOVE BURRS AND BREAK SHARP EDGES
2. ONE DECIMAL TOLERANCE  $\pm 0.6$  MM
3. INSIDE CORNER RADIUS OPTIONAL UP TO 2 MM
4. MATERIAL: AL ALY 7075-T7351. CHEMFILM PER MIL-C-5541 STRAW COLOR
5. ALL PARTS INCLUDING SINGLE PROTOTYPES SHALL BE MADE USING THE SAME METHODS WHICH WOULD BE USED FOR QUANTITIES OF 750 PARTS

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF TMT OBSERVATORY CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF TMT OBSERVATORY CORPORATION IS PROHIBITED.

METRIC		UNLESS OTHERWISE SPECIFIED:			TMT Observatory Corporation 2632 E. Washington Blvd. Pasadena, CA 91107		
THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS			TITLE:		
		TOLERANCES:			VERTICAL LINK CONNECT BLOCK		
		ANGULAR: MACH $\pm 0.5^\circ$			SIZE		
		TWO PLACE DECIMAL $\pm 0.3$			DWG. NO.		
		THREE PLACE DECIMAL $\pm 0.08$			REV		
		INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5M-1994			SCALE: 1:2		
		MATERIAL			WEIGHT:		
		NOTED			SHEET 1 OF 1		
		FINISH					
		NOTED					
		APPLICATION					
		DO NOT SCALE DRAWING					